

AIL LED range

INDELAGUE GROUP



HIGHTECH | LIGHTING SOLUTIONS

AIL LED range

• Dimmable version (DALI).

• 1 or 3 hours emergency for 1x58W.

In a close collaboration with our retail clients, we developed AIL LED to fulfil the needs of our customers. After many surveys, studies and tests we achieved the best solution for retail shops. The main goals for this fixture were the energy efficiency, easy installation, easy maintenance and to increase shoppers comfort and experience in stores.

You can choose between different types of mounting, powers and reflectors to suit different types of retail shops applications.


It's no secret that the longer shoppers stay in your store, the greater the chance they'll buy something.

Simplification, along with energy-efficient, long-lasting lighting solutions, can mean savings! Retail outlets operate seven days a week, even small gains in efficiency can lead to big cost reductions. Replacing outdated lighting systems with more efficient, environmentally-friendly solutions will reduce energy consumption and maintenance requirements. Using fewer lamp

types and standardised wattages can reduce complexity and make maintenance more manageable, too. It all adds up to big savings, and improved bottom lines.


Areas of Application: Industrial/retail.













- LED luminaire luminous flux up to 2730/5460/8190 Lm.
- 1x19W/1x39W/1x58W available.
- LED up to 108 Lm/W.
- Life 50000 Hours.
- Colour temperature 4000/3000K.
- CRI >80.

Optional:

- Dimmable version (DALI).
- 1 or 3 hours emergency for 1x58W.





Optic System Options



ACM - Symmetric reflector with opal diffuser



AWM - Asymmetric reflector with opal diffuser



AIL /E LED Line


Recessed CONTINUOUS LINE luminaire

- LED luminaire luminous flux up to 2730/5460/8190 Lm.
- 1x19W/1x39W/1x58W available.
- LED up to 108 Lm/W.
- Life 50000 Hours.
- Colour temperature 4000/3000K.
- CRI >80.

Optional:

- Dimmable version (DALI).
- 1 or 3 hours emergency for 1x58W.

PERFORMANCE



AIL /E LED Line ACM

1260

1120

LED: 1 x 58W SPACING: 17,5m x 10m CEILING HEIGHT: 4,5m MAINTENANCE: 0,8 REFLECTANCE: 20/70/50 WORKING PLACE: 1m ILLUMINANCE: 1044 lux INDELAGUE GROUP

INDELAGUE

HIGHTECH | LIGHTING SOLUTIONS



HEADQUARTERS

INDÚSTRIA ELÉTRICA DE ÁGUEDA S.A. Rua da Mina 465 | Covão Zona industrial EN1 Norte Apartado 106 / 3754-909 3750-792Trofa ÁGUEDA | PORTUGAL GPS. 40° 36′ 00.54″ N | 8° 27′ 11.76″ W T. +351 234 612 310 | F. +351 234 624 058 WWW.INDELAGUE.COM

UNITED KINGDOM

ROXO LIGHTING LIMITED 24 BEDFORD ROW LONDON | WC1R 4TQ roxo.london@roxolighting.com WWW.ROXOLIGHTING.COM

SPAIN

INDELAGUE ESPAÑA, S.L. Avenida del Ejército, nº 8 - 1°C C.P. 15006 | A CORUÑA | ESPAÑA comercial @ indelague.com WWW.INDELAGUE.COM







The company reserves the right to change specification without prior notification or public announcement.