

LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Indirect.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).


Optical System: Diffuser: Polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.


DPT - Transparent polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	kg	HF	DALI
	11	1290	116	99	350x250x108	1,8	90111.L112.E	90111.L212.H
	23	2580	107	95	350x250x108	1,8	90111.L212.E	90111.L212.H

COLOUR / FINISH


Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black
• Other colours under request.	

DIMENSIONS



OPTIONS

Colour temperature




3000K

Order code
3000

Example code for order: 90111.L112.H (DALI) + W (COLOUR/FINISH) + 3000 (OPTIONS).

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

DETAILS




LED detail




Product detail

PHOTOMETRY



ALEIK LED 11W
DOZ 4000K



ALEIK LED 23W
DOZ 4000K

TO SPECIFY:

LED wall mounted luminaire. Standard total luminous flux of 1290 or 2580 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Transparent polycarbonate diffuser for a homogeneous wall illumination through uniform indirect light distribution. Optional DALI dimmable driver and 3000K. - as Indelague ALEIK LED.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.