

LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Indirect.


Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 °C).

Optical System: Diffuser: polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

LED	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	HF	DALI
	23	2580	90	80	300x100x45	1,0	90163.L020.E	90163.L020.H
	37	5160	110	79	600x100x45	1,8	90163.L036.E	90163.L036.H

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black
• Other colours under request.	

DETAILS



Product detail

OPTIONS

Colour temperature




3000K

Order code
3000


Example code for order: 90163.L020.H (DALI) + W (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



DIMENSIONS



TO SPECIFY:

LED wall mounted luminaire. Flat design luminaire with DOZ opal polycarbonate diffuser for a homogeneous wall illumination through uniform indirect light distribution. Standard total luminous flux of 2580 or 5160 lm, 4000K, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25 C). Optional DALI dimmable driver and 3000K. - as Indelague AURA

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.