

**LED**

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Art and Culture spaces.

**Mounting:** Wall Mounted.

**Light Distribution:** Indirect.


**Light Source:** LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 °C).

**Optical System:** Diffuser: polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

LED	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	HF	DALI
	23	2580	90	80	300x100x45	1,0	90163.L020.E	90163.L020.H
	37	5160	110	79	600x100x45	1,8	90163.L036.E	90163.L036.H

**COLOUR / FINISH**

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black
• Other colours under request.	

**DETAILS**



Product detail

**OPTIONS**

**Colour temperature**



3000K

Order code  
**3000**

Example code for order: 90163.L020.H (DALI) + W (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

