



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 14° Beam angle

	LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
	LED	10	950	85	89	195x195x114	1,2	90390.L110.0.0014
		20	1900	76	80	195x195x114	1,2	90390.L120.0.0014
		30	2835	87	92	195x195x114	1,2	90390.L130.0.0014

PB - Polished aluminium reflector | 36° Beam angle

	LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
	LED	10	950	79	83	195x195x114	1,2	90390.L110.0.0036
		20	1900	77	81	195x195x114	1,2	90390.L120.0.0036
		30	2835	81	86	195x195x114	1,2	90390.L130.0.0036

PB 14 | PB 36
 • DIM version under request.

Please note:
 • To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:
 (1) Body colour finish
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90390.L110.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 971700 + 940400 + 910002 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Ceiling rose



Square recessed
Grey **971402**
White **971400**
Black **971401**
Square surface mounted
Grey **971702**
White **971700**
Black **971701**

Order code


Current supply cable



1,5m transparent cable 0,75mm2
3 x 0,75 mm2

Order code
940400


Suspension




Suspension type "I" (x4)

Order code
910002

PHOTOMETRY



AXIS Sq 1 10W
PB 4000K 14°



AXIS Sq 1 10W
PB 4000K 36°

TO SPECIFY:

Single square LED suspended spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 950, 1900 or 2835 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. Suspension kit, current supply cable and ceiling rose as accessories. - as Roxo Lighting AXIS Sq 1

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.