



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 14° Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	20	1900	85	89	355x195x114	2,1	90390.L220.0.0014
	40	3800	76	80	355x195x114	2,1	90390.L240.0.0014
	60	5670	87	92	355x195x114	2,1	90390.L260.0.0014

PB - Polished aluminium reflector | 36° Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	20	1900	79	83	355x195x114	2,1	90390.L220.0.0036
	40	3800	77	81	355x195x114	2,1	90390.L240.0.0036
	60	5670	81	86	355x195x114	2,1	90390.L260.0.0036


PB 14 | PB 36
 • DIM version under request.

Please note:

• To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:
 (1) Body colour finish
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90390.L110.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 971700 + 940400 + 910002 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS


Colour temperature



3000K

Order code
3000

Ceiling rose



Square recessed
Grey
White
Black
Square surface mounted
Grey
White
Black

Order code
971402
971400
971401
971702
971700
971701


Current supply cable



1,5m transparent cable 0,75mm²
3 x 0,75 mm²

Order code
940400

Suspension



Suspension type "I" (x4)

Order code
910002

TO SPECIFY:

Double square LED suspended spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 1900, 3800 or 5670 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. Suspension kit, current supply cable and ceiling rose as accessories. - as Roxo Lighting AXIS Sq 2

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.