



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 14° Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	30	2850	85	89	515x195x114	3,0	90390.L330.0.0014
	60	5700	76	80	515x195x114	3,0	90390.L360.0.0014
	90	8505	87	92	515x195x114	3,0	90390.L390.0.0014

PB - Polished aluminium reflector | 36° Beam angle


LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	30	2850	79	83	515x195x114	3,0	90390.L330.0.0036
	60	5700	77	81	515x195x114	3,0	90390.L360.0.0036
	90	8505	81	86	515x195x114	3,0	90390.L390.0.0036

PB 14 | PB 36
 • DIM version under request.

Please note:
 • To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:
 (1) Body colour finish
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90390.L110.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 971700 + 940400 + 910002 (OPTIONS)

We reserve the right to make technical changes without prior notice.
 Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Ceiling rose



Square recessed
Grey
White
Black
Square surface mounted
Grey
White
Black

Order code

971402
971400
971401
971702
971700
971701


Current supply cable



1,5m transparent cable 0,75mm2
3 x 0,75 mm2

Order code
940400

Suspension



Suspension type "I" (x4)

Order code

910002

TO SPECIFY:

Triple square LED suspended spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 2850, 5700 or 8505 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. Suspension kit, current supply cable and ceiling rose as accessories. - as Indelague AXIS Sq 3

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.