



**LED**

Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

**Control Gear:** COB LED 230V-50/60Hz

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

PB - Polished aluminium reflector | 14° Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	40	3800	85	89	355x355x114	3,8	90390.L440.0.0014
	80	7600	76	80	355x355x114	3,8	90390.L480.0.0014
	120	11340	87	92	355x355x114	3,8	90390.L412.0.0014

PB - Polished aluminium reflector | 36° Beam angle


LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	40	3800	79	83	355x355x114	3,8	90390.L440.0.0036
	80	7600	77	81	355x355x114	3,8	90390.L480.0.0036
	120	11340	81	86	355x355x114	3,8	90390.L412.0.0036

PB 14 | PB 36  
 DIM version under request.

Please note:  
 • To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

### COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:  
 (1) Body colour finish  
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

### DIMENSIONS



Example code for order: 90390.L110.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 971700 + 940400 + 910002 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**

**Colour temperature**



3000K

Order code  
**3000**

**Ceiling rose**



Square recessed  
Grey  
White  
Black  
Square surface mounted  
Grey  
White  
Black

Order code  
**971402**  
**971400**  
**971401**  
**971702**  
**971700**  
**971701**


**Current supply cable**



1,5m transparent cable 0,75mm<sup>2</sup>  
3 x 0,75 mm<sup>2</sup>

Order code  
**940400**

**Suspension**



Suspension type "I" (x4)

Order code  
**910002**

**TO SPECIFY:**

Quadruple square LED suspended spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 3800, 7600 or 11340 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. Suspension kit, current supply cable and ceiling rose as accessories. - as Roxo Lighting AXIS Sq 4

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.