



**LED**

Norms: EN 60598-1, EN 60598-2-1



### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Surface.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

**Control Gear:** COB LED 230V-50/60Hz

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

PB - Polished aluminium reflector | 14 Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	40	3800	85	89	369x369x160	7,6	90389.L440.0.0014
	80	7600	76	80	369x369x160	7,6	90389.L480.0.0014


PB - Polished aluminium reflector | 36 Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	40	3800	79	83	369x369x160	7,6	90389.L440.0.0036
	80	7600	77	81	369x369x160	7,6	90389.L480.0.0036

▬ PB 14 | PB 36  
 • DIM version under request.

### COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:  
 (1) Body colour finish  
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

### DIMENSIONS



Example code for order: 90389.L440.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.


## OPTIONS

### Colour temperature

Order code

3000K

3000



### TO SPECIFY:

Triple square LED surface spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 2850 or 5700 lm, 4000K, CRI>80 and 40.000h lifetime (@L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Roxo Lighting AXIS Sq /C 3

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.