



LED

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.



Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz



Materials: Body: Steel sheet.


Surface Finish: Powder coated.

PB - Polished aluminium reflector | 14° Beam angle




	LAMP	W	lm	lm/W	η(%)	AxBxC (mm)		kg	CÓDIGO
	LED	20	1900	85	89	371x215x120	355x200	2,9	90388.L220.0.0014
		40	3800	76	80	371x215x120	355x200	2,9	90388.L240.0.0014
		60	5670	87	92	371x215x120	355x200	2,9	90388.L260.0.0014


PB - Polished aluminium reflector | 36° Beam angle

	LAMP	W	lm	lm/W	η(%)	AxBxC (mm)		kg	CÓDIGO
	LED	20	1900	79	83	371x215x120	355x200	2,9	90388.L220.0.0036
		40	3800	77	81	371x215x120	355x200	2,9	90388.L240.0.0036
		60	5670	81	86	371x215x120	355x200	2,9	90388.L260.0.0036

 PB 14 | PB 36
 • DIM version under request.

COLOUR / FINISH


Code	Description
 W/B	(1) White / (2) Black
 G/B	(1) Grey / (2) Black
 B/B	(1) Black / (2) Black



Subtitle:
 (1) Trim colour finish
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the trim colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90388.L220.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K


Order code
3000

Steel safety cable

Steel safety cable

Order code
955000

Emergency unit



Option supplied under request.

TO SPECIFY:

Double square LED recessed spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 1900, 3800 or 5670 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Roxo Lighting AXIS Sq /E 2

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.