



LED

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.



Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz



Materials: Body: Extruded aluminium.


Surface Finish: Powder coated.

PB - Polished aluminium reflector | 14° Beam angle




	LED	W	lm	lm/W	η(%)	AxBxC (mm)		kg	CÓDIGO
		30	2850	85	89	527x215x120	510x200	4,3	90388.L330.0.0014
		60	5700	76	80	527x215x120	510x200	4,3	90388.L360.0.0014
		90	8505	87	92	527x215x120	510x200	4,3	90388.L390.0.0014


PB - Polished aluminium reflector | 36° Beam angle

	LED	W	lm	lm/W	η(%)	AxBxC (mm)		kg	CÓDIGO
		30	2850	79	83	527x215x120	510x200	4,3	90388.L330.0.0036
		60	5700	77	81	527x215x120	510x200	4,3	90388.L360.0.0036
		90	8505	81	86	527x215x120	510x200	4,3	90388.L390.0.0036

 PB 14 | PB 36
• DIM version under request.

COLOUR / FINISH


Code	Description
 W/B	(1) White / (2) Black
 G/B	(1) Grey / (2) Black
 B/B	(1) Black / (2) Black



Subtitle:
(1) Trim colour finish
(2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the trim colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90388.L330.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000


Steel safety cable



Steel safety cable

Order code
955000

Emergency unit



Option supplied under request.

TO SPECIFY:

Triple square LED recessed spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 2850, 5700 or 8505 lm, 4000K, CRI>80 and 40.000h lifetime (@L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Indelague AXIS Sq /E 3

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.