



LED

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 14° Beam angle

LED	W	lm	lm/W	η(%)	AxBxC (mm)	Beam	kg	CÓDIGO
	30	2850	85	89	527x215x120	510x200	4,3	90388.L330.0.0014
	60	5700	76	80	527x215x120	510x200	4,3	90388.L360.0.0014
	90	8505	87	92	527x215x120	510x200	4,3	90388.L390.0.0014


PB - Polished aluminium reflector | 36° Beam angle

LED	W	lm	lm/W	η(%)	AxBxC (mm)	Beam	kg	CÓDIGO
	30	2850	79	83	527x215x120	510x200	4,3	90388.L330.0.0036
	60	5700	77	81	527x215x120	510x200	4,3	90388.L360.0.0036
	90	8505	81	86	527x215x120	510x200	4,3	90388.L390.0.0036

PB 14 | PB 36
• DIM version under request.

COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:
(1) Trim colour finish
(2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the trim colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90388.L330.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000

Steel safety cable



Steel safety cable

Order code
955000

Emergency unit



Option supplied under request.

TO SPECIFY:

Triple square LED recessed spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 2850, 5700 or 8505 lm, 4000K, CRI>80 and 40.000h lifetime (@L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Roxo Lighting AXIS Sq /E 3

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.