



**LED**

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

### PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Ceiling recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 50.000h life (@L70, B50, Ta 25 C).

**Control Gear:** COB LED 230V-50/60Hz

**Materials:** Body: Steel sheet.

**Surface Finish:** Powder coated.

**Fixing system:** Trimless brackets.

PB - Polished aluminium reflector | 14° Beam angle

	LAMP	W	Lm	Lm/W	η(%)	AxBxC (mm)		Kg	ORDER CODE
	LED	10	950	85	89	175x175x127	176x176	1,2	90387.L110.0.0014
		20	1900	76	80	175x175x127	176x176	1,2	90387.L120.0.0014
		30	2835	87	92	175x175x127	176x176	1,2	90387.L130.0.0014

PB - Polished aluminium reflector | 36° Beam angle

	LAMP	W	Lm	Lm/W	η(%)	AxBxC (mm)		Kg	ORDER CODE
	LED	10	950	79	83	175x175x127	176x176	1,2	90387.L110.0.0036
		20	1900	77	81	175x175x127	176x176	1,2	90387.L120.0.0036
		30	2835	81	86	175x175x127	176x176	1,2	90387.L130.0.0036

PB 14 | PB 36  
 • Possibilidade de DIM sob consulta.

### COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
G/B	(1) Grey / (2) Black
B/B	(1) Black / (2) Black



Subtitle:  
 (1) Body colour finish  
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

### DIMENSIONS



Example code for order: 90387.L110.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### OPTIONS

#### Colour temperature



3000K

Order code  
**3000**


#### Steel safety cable



Steel safety cable


Order code  
**955000**

#### Emergency unit




Option supplied under request.

### PHOTOMETRY



AXIS Sq/T 1 10W  
PB 4000K 14°



AXIS Sq/T 1 10W  
PB 4000K 36°

#### TO SPECIFY:

Single square LED recessed trimless spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 950, 1900 or 2835 lm, 4000K, CRI>80 and 40000h lifetime (@L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Indelague AXIS Sq/T 1

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.