

LED

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).



Control Gear: COB LED 230V-50/60Hz

Materials: Body: Steel sheet.



Surface Finish: Powder coated.



Fixing system: Trimless brackets.

PB - Polished aluminium reflector | 14° Beam angle




	LAMP	W	Lm	Lm/W	η(%)	AxBxC (mm)		Kg	ORDER CODE
	LED	20	1900	85	89	331x175x127	332x176	2,1	90387.L220.0.0014
		40	3800	76	80	331x175x127	332x176	2,1	90387.L240.0.0014
		60	5670	87	92	331x175x127	332x176	2,1	90387.L260.0.0014


PB - Polished aluminium reflector | 36° Beam angle

	LAMP	W	Lm	Lm/W	η(%)	AxBxC (mm)		Kg	CODE COM.
	LED	20	1900	79	83	331x175x127	332x176	2,1	90387.L220.0.0036
		40	3800	77	81	331x175x127	332x176	2,1	90387.L240.0.0036
		60	5670	81	86	331x175x127	332x176	2,1	90387.L260.0.0036

 PB 14 | PB 36
 • DIM version under request.

COLOUR / FINISH


Code	Description
 W/B	(1) White / (2) Black
 G/B	(1) Grey / (2) Black
 B/B	(1) Black / (2) Black



Subtitle:
 (1) Body colour finish
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90387.L220.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice.
 Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K

Order code
3000


Steel safety cable



Steel safety cable

Order code
955000

Emergency unit



Option supplied under request.

TO SPECIFY:

Double square LED recessed trimless spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 1900, 3800 or 5670 lm, 4000K, CRI>80 and 40000h lifetime (@ L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Indelague AXIS Sq /T 2

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.