



LED

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

Fixing system: Trimless brackets.

PB - Polished aluminium reflector | 14° Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	□	kg	ORDER CODE
LED	40	3800	85	89	331x331x127	332x332	3,7	90387.L440.0.0014
	80	7600	76	80	331x331x127	332x332	3,7	90387.L480.0.0014
	120	11340	87	92	331x331x127	332x332	3,7	90387.L412.0.0014


PB - Polished aluminium reflector | 36° Beam angle

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	□	kg	ORDER CODE
LED	40	3800	79	83	331x331x127	332x332	3,7	90387.L440.0.0036
	80	7600	77	81	331x331x127	332x332	3,7	90387.L480.0.0036
	120	11340	81	86	331x331x127	332x332	3,7	90387.L412.0.0036

▬ ▬ ▬ PB 14 | PB 36
 - + • DIM version under request.

COLOUR / FINISH


Code	Description
■ W/B	(1) White / (2) Black
■ G/B	(1) Grey / (2) Black
■ B/B	(1) Black / (2) Black



Subtitle:
 (1) Body colour finish
 (2) Gimbal colour finish

• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the gimbal colour finish.

DIMENSIONS



Example code for order: 90387.L440.0.0036 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 + 955000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature



3000K


Order code
3000

Steel safety cable

Steel safety cable

Order code
955000

Emergency unit



Option supplied under request.

TO SPECIFY:

Quadruple square LED recessed trimless spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 3800, 7600 or 11340 lm, 4000K, CRI>80 and 40000h lifetime (@ L70, B50, Ta 25 °C) and passive cooling of the LED through improved heat sink. Spotlight can be adjusted in any direction through the gimbal system that tilts 25°. Optional 3000K. - as Roxo Lighting AXIS Sq /T 4.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.