

LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Track spotlight.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L70, B50, Ta 25 C).


Control Gear: COB LED 230V-50/60Hz

Materials: Body: Extruded aluminium.


Surface Finish: Powder coated.




PB - Polished aluminium reflector | 14 Beam angle

	LAMP	W	lm	lm/W	η(%)	AxB (mm)	kg	CÓDIGO
	LED	10	950	85	89	95x152	0,6	90392.L110.0.0014
		20	1900	76	80	95x152	0,6	90392.L120.0.0014
		30	2835	87	92	95x152	0,6	90392.L130.0.0014

PB - Polished aluminium reflector | 36 Beam angle

	LAMP	W	lm	lm/W	η(%)	AxB (mm)	kg	CÓDIGO
	LED	10	950	79	83	95x152	0,6	90392.L110.0.0036
		20	1900	77	81	95x152	0,6	90392.L120.0.0036
		30	2835	81	86	95x152	1,2	90392.L130.0.0036

 PB 14 | PB 36
• DIM version under request.

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

• Other colours under request.

DIMENSIONS




Example code for order: 90392.L110.0.0036 (ORDER CODE) + B (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS


Colour temperature



3000K


Order code
3000

Track system




Option supplied under request.

PHOTOMETRY



**AXIS Track 30W
PB 4000K 14°**



**AXIS Track 30W
PB 4000K 36°**

PERFORMANCE

0,5 m	42674 lux	0,18 m
1,0 m	10668 lux	0,36 m
1,5 m	4742 lux	0,54 m
2,0 m	2667 lux	0,73 m
2,5 m	1707 lux	0,91 m
3,0 m	1185 lux	1,09 m

**AXIS Track 30W
PB 4000K 14°**

0,5 m	16761 lux	0,37 m
1,0 m	4190 lux	0,74 m
1,5 m	1862 lux	1,11 m
2,0 m	1049 lux	1,48 m
2,5 m	670 lux	1,85 m
3,0 m	466 lux	2,22 m

**AXIS Track 30W
PB 4000K 36°**

TO SPECIFY:

LED track spotlight. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angles of 14° or 36°. Multifunctional spotlight for precise and adjustable accent lighting. Standard total luminous flux of 950, 1900 or 2835 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Spotlight body rotates 355° and tilts 90°. Optional 3000K. - as Indelague AXIS Track

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.