



LED



Norms: EN 60598-1, EN 60598-2-1



IP 20

0,5mE

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface/Suspended.

Light Distribution: Direct.


Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 36 Beam angle



	LAMP	W	Lm	Lm/W	η(%)	AxB (mm)	kg	ORDER CODE
	LED	10	950	75	79	Ø95x150	0,8	90016.L165.0
		10	950	75	79	Ø95x230	0,9	90016.L245.0
		10	950	75	79	Ø95x310	1,0	90016.L325.0

 • DIM version under request.

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

DIMENSIONS



Example code for order: 90016.L325.0 (ORDER CODE) + W (COLOUR/FINISH) + 3000 + 911500 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS


Colour temperature



3000K

Order code
3000


Suspension kit



	Order code
Recessed	
White	911500
Grey	911502
Black	911501
Surface mounted	
White	911600
Grey	911602
Black	911601

• Transparent current supply cable and ceiling rose included. Surface mounted version with white colour (body) and black colour (upper face).

PHOTOMETRY



BATU 10W
PB (230mm) 4000K 36°

TO SPECIFY:

Circular LED surface mounted or suspended spotlight. Aluminium body, powder coated in epoxy polyester. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angle of 36°. Standard total luminous flux of 950 lm, 4000K, CRI>80 and 40000h lifetime (@ L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Multiple colours available. Optional 3000K. - as Roxo Lighting BATU

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.