



LED

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Art and Culture spaces.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

**Control Gear:** COB LED 230V-50/60Hz

**Materials:** Body: Extruded aluminium.

**Surface Finish:** Powder coated.


PB - Polished aluminium reflector | 36 Beam angle

LED	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	ORDER CODE
	10	950	75	79	100x100x158	1,0	90025.L165.0
	10	950	75	79	100x100x238	1,2	90025.L245.0
	10	950	75	79	100x100x318	1,6	90025.L325.0

PW  
• DIM version under request.




**COLOUR / FINISH**

Code	Description
W/B	(1) White / (2) Black
W/W	(1) White / (2) White
G/G	(1) Grey/ (2) Grey
B/B	(1) Black / (2) Black



Subtitle:  
(1) Body colour finish  
(2) Inside trim colour finish  
• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the inside trim colour finish.

**DIMENSIONS**



Example code for order: 90025.L165.0 (ORDER CODE) + 9113 + 3000 (OPÇÕES)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**

**Colour temperature**



3000K

Order code  
**3000**

**Suspension kit**




Recessed  
Surface mounted

• Transparent current supply cable and ceiling rose included. Please add ceiling rose colour.

Order code  
**9113**  
**9114**

**PHOTOMETRY**



**BATU Sq 10W**  
**PB (238mm) 4000K 36°**

**TO SPECIFY:**

Square LED surface mounted or suspended spotlight. Aluminium body, powder coated in epoxy polyester. Equipped with the latest LED technology and PB high performance aluminum reflectors with excellent reflection properties, beam angle of 36°. Standard total luminous flux of 950 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Multiple colours available. Optional 3000K and suspension kit. - as Indelague BATU Sq

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.