



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Direct / Indirect.

Light Source: LED 4000K, CRI>80, 40.000h life (@L70, B50, Ta 25 C).

Control Gear: COB LED 230V-50/60Hz

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.


PW - White aluminium reflector | 80 +80 Beam angle | 50% (Direct) + 50% (Indirect)

LAMP	W	lm	lm/W	η(%)	AxBxC (mm)	kg	ORDER CODE
LED	20	1900	75	79	120x100x150	1,2	90029.L150.0

PW
+ DIM version under request.

COLOUR / FINISH


Code	Description
W/B	(1) White / (2) Black
W/W	(1) White / (2) White
G/G	(1) Grey / (2) Grey
B/B	(1) Black / (2) Black



Subtitle:
(1) Body colour finish
(2) Inside trim colour finish


• The finish order code is based on two colours, where (1) is the body colour finish and (2) is the inside trim colour finish.

DIMENSIONS



OPTIONS

Colour temperature




3000K

Order code
3000

Example code for order: 90029.L150.0 (ORDER CODE) + W/B (COLOUR/FINISH) + 3000 (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



BATU Sq/W 20W
4000K 80°+80°

TO SPECIFY:

Square LED wall mounted, direct/indirect luminaire. Aluminium body, powder coated in epoxy-polyester. Equipped with the latest LED technology and PW high performance aluminum reflectors with excellent reflection properties, beam angle of 80 +80 . Standard total luminous flux of 1900 lm, 4000K, CRI>80 and 40.000h lifetime (@ L70, B50, Ta 25 C) and passive cooling of the LED through improved heat sink. Multiple colours configurations available. Optional 3000K. - as Indelague BATU Sq/W

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.