



LED

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial, Business areas, Housing, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

**Mounting:** Suspended.

**Light Distribution:** Direct / Indirect.

**Light Source:** LED 4000K, RG1, CRI>80, MacAdam Step <3, 90.000h lifetime (@L80, B10, Ta25 C).

**Optical System:** Diffuser: Microprismatic or Opal.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Extruded aluminium.

**Surface Finish:** Powder coated.

gCONTROL+ - Microprismatic diffuser PLUS | 80% (Direct) + 20% (Indirect)

LAMP	UGR	W	Lm Output	lm/W	D (mm)	K3	kg	HF	DALI
LED	≤19	43	4043	94	Ø600	-	-	90626L600E	90626L600H
	≤16	62	6192	100	Ø900	•	-	90626L900E	90626L900H
	≤16	91	8932	98	Ø1200	•	-	90626L120E	90626L120H
	≤16	108	11130	103	Ø1500	•	-	90626L150E	90626L150H

LIGHT+ - Opal diffuser | 80% (Direct) + 20% (Indirect)


LAMP	UGR	W	Lm Output	lm/W	D (mm)	K3	kg	HF	DALI
LED	≤22	43	4337	101	Ø600	-	-	90636L600E	90636L600H
	≤19	62	6512	105	Ø900	•	-	90636L900E	90636L900H
	≤19	91	9548	105	Ø1200	•	-	90636L120E	90636L120H
	≤19	108	11501	106	Ø1500	•	-	90636L150E	90636L150H

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
U	Blue
V	Green
T	Yellow
K	Red
N	Jungle
D	Golden eye
O	Sahara
L	Autumn
R	Rusty chain
C	Pure chocolate
1	Mist
9	Dark rock
I	Carbon

### DIMENSIONS



Recessed ceiling rose  
T5 D90



Surface mounted ceiling rose  
T24 D95



Central ceiling rose  
T21 D95



### OPTIONS

#### Colour temperature



3000K

Order Code

**3000**

#### Ceiling rose



Ceiling rose  
Surface T24 D95  
Recessed T5 D90

Order Code

**978600**  
**9713**

Surface T26 D95 (DALI + K3)  
Recessed T27 D90 (DALI + K3)

**978601**  
**978700**

To order this option indicate the required colour for the ceiling rose.

#### Central Ceiling Rose



Central Ceiling Rose T21 3I D95  
Central Ceiling Rose T28 3I D95 (DALI + K3)

Order Code

**977211**  
**977230**

• To order this option indicate the required colour for the ceiling rose.

#### Current supply cable




Transparent current supply cable with 1,5m  
3 x 0,75 mm2  
5 x 0,75 mm2  
7 x 0,75 mm2

Order Code

**940400**  
**940500**  
**940600**

• For dimmable Dali with emergency unit and with remote-control, it is necessary to order 2 current supply cables of 5x0,75 mm2.

#### Suspension



Suspension S10 L1500 (x3)

Order code

**9111001**

• Lengths of 3000mm and 6000mm under request.

#### Bluetooth module



Bluetooth module  
controllable through smartphone.

Order code

**927200**

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### Emergency unit

Order code




Emergency unit 3 hours

K3

- Prepared for Remote-control.


### DETAILS



gCONTROL+  
diffuser



LIGHT+ diffuser



Indirect part



Suspended  
application for  
central ceiling rose



Central ceiling rose  
T21



Suspended  
application for  
perpendicular  
suspensions




Recessed ceiling  
rose T5




Surface mounted  
ceiling rose T24

### PHOTOMETRY



CONCEPT O 65 D/I  
gCONTROL+



CONCEPT O 65 D/I  
LIGHT+

### TO SPECIFY:

Suspended circular LED luminaire, with direct and indirect light. Powder coated extruded aluminium body, available in 16 different colours. Available in 4 diameters, 600, 900, 1200 and 1500mm, equipped with opal acrylic diffuser (PMMA) for a homogeneous light diffusion or with microprismatic diffuser for glare control. Standard version with LED 4000K, RG1 (Photobiological Risk Group 1, according to IEC 62471), CRI>80, 90.000h lifetime (@L80, B10, Ta 25 C). Optional dimmable DALI driver, 3h emergency unit, 3000K, S10 suspension and transparent current supply cable. Possible to include recessed ceiling rose T5 D90 or surface ceiling rose T24 D95 and surface central ceiling rose T21. – as Roxo Lighting CONCEPT O 65 D/I.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.