

PHOTOMETRIC RESULTS

Name:	CORA /E L60W60 3 BOPTICS K3 840 LO		
Number:	90726Q360	Diameter:	0 mm
Report:	24-10-2022	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	25 mm
Number:	1	Power:	18,33 W
Lamp flux:	2880,00 lm	Operator:	INDELAGUE GROUP
Date:	24/10/2022 16:30:49	Output ratio:	81,4 %


Info

LiTG-class:	A60									
UTE-class:	Not available									
IES-class:	99 - 100 - 100 - 100 - 81									
TM5-class:	BZ1									
Divergences in the plane through maximum intensity:						Horizontal		Vertical		
One half peak divergence:						43,5°		43,3°		
Half peak side angle (left):						-21,2°		-21,4°		
Half peak side angle (right):						22,3°		21,9°		
One tenth peak divergence:						65,2°		65,1°		
Tenth peak side angle (left):						-32,6°		-32,3°		
Tenth peak side angle (right):						32,6°		32,9°		
C-planes:	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						
Gamma:	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	

PHOTOMETRIC RESULTS

Name:	CORA /E L60W60 3 BOPTICS K3 840 LO		
Number:	90726Q360	Diameter:	0 mm
Report:	24-10-2022	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	25 mm
Number:	1	Power:	18,33 W
Lamp flux:	2880,00 lm	Operator:	INDELAGUE GROUP
Date:	24/10/2022 16:30:49	Output ratio:	81,4 %

Polar diagram CORA /E L60W60 3 BOPTICS K3 840 LO / Direct in 15° C / 5° G



PHOTOMETRIC RESULTS

Name:	CORA /E L60W60 3 BOPTICS K3 840 LO			
Number:	90726Q360	Diameter:	0 mm	
Report:	24-10-2022	Length:	597 mm	
Meas.-no.:	01	Width:	597 mm	
Lamp type:	LED 840 - 01	Height:	25 mm	
Number:	1	Power:	18,33 W	
Lamp flux:	2880,00 lm	Operator:	INDELAGUE GROUP	
Date:	24/10/2022 16:30:49	Output ratio:	81,4 %	

UGR Unified Glare Ratios

Ceiling reflectance	0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance	0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension	Viewed crosswise					Viewed endwise				
2H	2H	1,9	2,6	2,2	2,9	3,2	2,0	2,7	2,3	3,0
2H	3H	1,6	2,2	2,0	2,6	2,9	1,7	2,3	2,1	2,7
2H	4H	1,5	2,1	1,9	2,4	2,8	1,6	2,2	2,0	2,5
2H	6H	1,4	1,9	1,8	2,3	2,7	1,5	2,0	1,9	2,4
2H	8H	1,3	1,8	1,7	2,2	2,6	1,4	1,9	1,8	2,3
2H	12H	1,2	1,7	1,6	2,1	2,5	1,3	1,8	1,7	2,2
4H	2H	1,5	2,1	1,9	2,4	2,8	1,6	2,2	2,0	2,5
4H	3H	1,2	1,7	1,6	2,1	2,5	1,3	1,8	1,7	2,2
4H	4H	1,1	1,5	1,5	1,9	2,4	1,2	1,6	1,6	2,0
4H	6H	0,9	1,3	1,4	1,8	2,2	1,0	1,4	1,5	1,9
4H	8H	0,8	1,2	1,3	1,7	2,1	0,9	1,3	1,4	1,8
4H	12H	0,8	1,1	1,3	1,6	2,1	0,9	1,2	1,4	1,7
8H	4H	0,8	1,2	1,3	1,7	2,1	0,9	1,3	1,4	1,8
8H	6H	0,6	1,0	1,2	1,4	1,9	0,7	1,1	1,3	1,5
8H	8H	0,6	0,9	1,2	1,4	1,9	0,7	1,0	1,3	1,5
8H	12H	0,6	0,8	1,1	1,3	1,8	0,7	0,9	1,2	1,4
12H	4H	0,8	1,1	1,3	1,6	2,1	0,9	1,2	1,4	1,7
12H	6H	0,6	0,9	1,1	1,4	1,9	0,7	1,0	1,2	1,5
12H	8H	0,5	0,7	1,1	1,3	1,8	0,6	0,8	1,2	1,4

UGR values are corrected for lamp flux of 2880 lm by 3,7

PHOTOMETRIC RESULTS

Name:	CORA /E L60W60 3 BOPTICS K3 840 LO		
Number:	90726Q360	Diameter:	0 mm
Report:	24-10-2022	Length:	597 mm
Meas.-no.:	01	Width:	597 mm
Lamp type:	LED 840 - 01	Height:	25 mm
Number:	1	Power:	18,33 W
Lamp flux:	2880,00 lm	Operator:	INDELAGUE GROUP
Date:	24/10/2022 16:30:49	Output ratio:	81,4 %

Luminance [cd/m²] CORA /E L60W60 3 BOPTICS K3 840 LO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	26,14	30,16	41,24	53,27	48,29	36,18	34,17	36,18	48,29
50,00	13,27	14,38	17,70	23,22	22,13	17,69	17,69	17,69	22,13
55,00	7,44	9,91	9,92	13,63	13,64	9,91	9,91	9,91	13,64
60,00	5,69	5,69	5,69	5,69	7,11	5,68	5,69	5,68	7,11
65,00	6,73	6,73	6,73	6,73	6,73	6,73	6,73	6,73	6,73
70,00	8,31	8,31	8,32	8,31	8,32	8,31	8,31	8,31	8,32
75,00	10,99	10,99	10,99	10,98	10,99	10,98	10,98	10,98	10,99
80,00	8,19	16,37	16,38	16,37	16,39	16,37	16,37	16,37	16,39
85,00	32,63	32,62	32,64	32,62	32,65	32,61	32,62	32,61	32,65

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	53,27	41,24	30,16	26,14	30,16	41,24	53,27	48,29	36,18
50,00	23,22	17,70	14,38	13,27	14,38	17,70	23,22	22,13	17,69
55,00	13,63	9,92	9,91	7,44	9,91	9,92	13,63	13,64	9,91
60,00	5,69	5,69	5,69	5,69	5,69	5,69	5,69	7,11	5,68
65,00	6,73	6,73	6,73	6,73	6,73	6,73	6,73	6,73	6,73
70,00	8,31	8,32	8,31	8,31	8,31	8,32	8,31	8,32	8,31
75,00	10,98	10,99	10,99	10,99	10,99	10,99	10,98	10,99	10,98
80,00	16,37	16,38	16,37	8,19	16,37	16,38	16,37	16,39	16,37
85,00	32,62	32,64	32,62	32,63	32,62	32,64	32,62	32,65	32,61

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	34,17	36,18	48,29	53,27	41,24	30,16
50,00	17,69	17,69	22,13	23,22	17,70	14,38
55,00	9,91	9,91	13,64	13,63	9,92	9,91
60,00	5,69	5,68	7,11	5,69	5,69	5,69
65,00	6,73	6,73	6,73	6,73	6,73	6,73
70,00	8,31	8,31	8,32	8,31	8,32	8,31
75,00	10,98	10,98	10,99	10,98	10,99	10,99
80,00	16,37	16,37	16,39	16,37	16,38	16,37
85,00	32,62	32,61	32,65	32,62	32,64	32,62