

## PHOTOMETRIC RESULTS

<b>Name:</b>	CORA L90W30 2 BOPTICS 830 LO		
<b>Number:</b>	90724L290	<b>Diameter:</b>	0 mm
<b>Report:</b>	20-10-2022	<b>Length:</b>	897 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	297 mm
<b>Lamp type:</b>	LED 830 - 01	<b>Height:</b>	30 mm
<b>Number:</b>	1	<b>Power:</b>	19,84 W
<b>Lamp flux:</b>	2950,00 lm	<b>Operator:</b>	INDELAGUE GROUP
<b>Date:</b>	20/10/2022 14:42:45	<b>Output ratio:</b>	82,5 %


## Info

<b>LiTG-class:</b>	A60									
<b>UTE-class:</b>	Not available									
<b>IES-class:</b>	99 - 100 - 100 - 100 - 82									
<b>TM5-class:</b>	BZ1									
<b>Divergences in the plane through maximum intensity:</b>						Horizontal		Vertical		
<b>One half peak divergence:</b>						46,1°		45,9°		
<b>Half peak side angle (left):</b>						-23,2°		-23,3°		
<b>Half peak side angle (right):</b>						22,9°		22,6°		
<b>One tenth peak divergence:</b>						67,8°		67,4°		
<b>Tenth peak side angle (left):</b>						-34,1°		-33,7°		
<b>Tenth peak side angle (right):</b>						33,7°		33,6°		
<b>C-planes:</b>	0,0°	15,0°	30,0°	45,0°	60,0°	75,0°	90,0°	105,0°	120,0°	135,0°
	150,0°	165,0°	180,0°	195,0°	210,0°	225,0°	240,0°	255,0°	270,0°	285,0°
	300,0°	315,0°	330,0°	345,0°						
<b>Gamma:</b>	0,0°	5,0°	10,0°	15,0°	20,0°	25,0°	30,0°	35,0°	40,0°	45,0°
	50,0°	55,0°	60,0°	65,0°	70,0°	75,0°	80,0°	85,0°	90,0°	

## PHOTOMETRIC RESULTS

Name:	CORA L90W30 2 BOPTICS 830 LO		
Number:	90724L290	Diameter:	0 mm
Report:	20-10-2022	Length:	897 mm
Meas.-no.:	01	Width:	297 mm
Lamp type:	LED 830 - 01	Height:	30 mm
Number:	1	Power:	19,84 W
Lamp flux:	2950,00 lm	Operator:	INDELAGUE GROUP
Date:	20/10/2022 14:42:45	Output ratio:	82,5 %

Polar diagram CORA L90W30 2 BOPTICS 830 LO / Direct in 15° C / 5° G



## PHOTOMETRIC RESULTS

<b>Name:</b>	CORA L90W30 2 BOPTICS 830 LO			
<b>Number:</b>	90724L290	<b>Diameter:</b>	0 mm	
<b>Report:</b>	20-10-2022	<b>Length:</b>	897 mm	
<b>Meas.-no.:</b>	01	<b>Width:</b>	297 mm	
<b>Lamp type:</b>	LED 830 - 01	<b>Height:</b>	30 mm	
<b>Number:</b>	1	<b>Power:</b>	19,84 W	
<b>Lamp flux:</b>	2950,00 lm	<b>Operator:</b>	INDELAGUE GROUP	
<b>Date:</b>	20/10/2022 14:42:45	<b>Output ratio:</b>	82,5 %	

## UGR Unified Glare Ratios

Ceiling reflectance		0,7	0,7	0,5	0,5	0,3	0,7	0,7	0,5	0,5	0,3
Wall reflectance		0,5	0,3	0,5	0,3	0,3	0,5	0,3	0,5	0,3	0,3
Floor cavity reflectance		0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2
Room dimension		Viewed crosswise					Viewed endwise				
2H	2H	4,5	5,2	4,8	5,5	5,9	4,8	5,6	5,2	5,9	6,2
2H	3H	4,2	4,9	4,6	5,2	5,6	4,6	5,3	5,0	5,6	6,0
2H	4H	4,1	4,7	4,5	5,1	5,5	4,5	5,1	4,9	5,5	5,8
2H	6H	4,0	4,6	4,4	4,9	5,3	4,4	4,9	4,8	5,3	5,7
2H	8H	3,9	4,4	4,3	4,8	5,2	4,3	4,8	4,7	5,2	5,6
2H	12H	3,8	4,3	4,2	4,7	5,2	4,2	4,7	4,6	5,1	5,5
4H	2H	4,1	4,7	4,5	5,1	5,5	4,5	5,1	4,9	5,5	5,8
4H	3H	3,8	4,3	4,2	4,7	5,2	4,2	4,7	4,6	5,1	5,5
4H	4H	3,7	4,2	4,2	4,6	5,0	4,1	4,5	4,5	5,0	5,4
4H	6H	3,5	3,9	4,0	4,4	4,9	3,9	4,3	4,4	4,8	5,2
4H	8H	3,5	3,8	4,0	4,3	4,8	3,8	4,2	4,3	4,7	5,1
4H	12H	3,4	3,7	3,9	4,2	4,7	3,8	4,1	4,3	4,6	5,1
8H	4H	3,5	3,8	4,0	4,3	4,8	3,8	4,2	4,3	4,7	5,1
8H	6H	3,3	3,6	3,8	4,1	4,6	3,6	4,0	4,2	4,4	5,0
8H	8H	3,2	3,5	3,8	4,0	4,5	3,6	3,9	4,1	4,4	4,9
8H	12H	3,2	3,4	3,7	3,9	4,4	3,5	3,7	4,1	4,3	4,8
12H	4H	3,4	3,7	3,9	4,2	4,7	3,8	4,1	4,3	4,6	5,1
12H	6H	3,2	3,5	3,8	4,0	4,5	3,6	3,9	4,1	4,4	4,9
12H	8H	3,2	3,4	3,7	3,9	4,4	3,5	3,7	4,1	4,3	4,8

UGR values are corrected for lamp flux of 2950 lm by 3,8

## PHOTOMETRIC RESULTS

<b>Name:</b>	CORA L90W30 2 BOPTICS 830 LO		
<b>Number:</b>	90724L290	<b>Diameter:</b>	0 mm
<b>Report:</b>	20-10-2022	<b>Length:</b>	897 mm
<b>Meas.-no.:</b>	01	<b>Width:</b>	297 mm
<b>Lamp type:</b>	LED 830 - 01	<b>Height:</b>	30 mm
<b>Number:</b>	1	<b>Power:</b>	19,84 W
<b>Lamp flux:</b>	2950,00 lm	<b>Operator:</b>	INDELAGUE GROUP
<b>Date:</b>	20/10/2022 14:42:45	<b>Output ratio:</b>	82,5 %

Luminance [cd/m<sup>2</sup>] CORA L90W30 2 BOPTICS 830 LO / Direct in 15° C / 5° G

G/C [cd]	0,00	15,00	30,00	45,00	60,00	75,00	90,00	105,00	120,00
45,00	72,66	86,92	115,39	150,12	134,36	104,30	91,68	104,30	134,36
50,00	27,80	33,03	43,47	55,63	48,69	39,99	38,25	39,99	48,69
55,00	15,58	15,59	21,44	29,22	25,33	23,38	19,49	23,38	25,33
60,00	4,47	8,94	8,94	15,64	15,65	8,94	8,94	8,94	15,65
65,00	0,00	2,64	5,29	10,58	7,94	2,64	5,29	2,64	7,94
70,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
75,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
80,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
85,00	0,00	12,82	0,00	0,00	0,00	12,82	0,00	12,82	0,00

G/C [cd]	135,00	150,00	165,00	180,00	195,00	210,00	225,00	240,00	255,00
45,00	150,12	115,39	86,92	72,66	86,92	115,39	150,12	134,36	104,30
50,00	55,63	43,47	33,03	27,80	33,03	43,47	55,63	48,69	39,99
55,00	29,22	21,44	15,59	15,58	15,59	21,44	29,22	25,33	23,38
60,00	15,64	8,94	8,94	4,47	8,94	8,94	15,64	15,65	8,94
65,00	10,58	5,29	2,64	0,00	2,64	5,29	10,58	7,94	2,64
70,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
75,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
80,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00
85,00	0,00	0,00	12,82	0,00	12,82	0,00	0,00	0,00	12,82

G/C [cd]	270,00	285,00	300,00	315,00	330,00	345,00
45,00	91,68	104,30	134,36	150,12	115,39	86,92
50,00	38,25	39,99	48,69	55,63	43,47	33,03
55,00	19,49	23,38	25,33	29,22	21,44	15,59
60,00	8,94	8,94	15,65	15,64	8,94	8,94
65,00	5,29	2,64	7,94	10,58	5,29	2,64
70,00	0,00	0,00	0,00	0,00	0,00	0,00
75,00	0,00	0,00	0,00	0,00	0,00	0,00
80,00	0,00	0,00	0,00	0,00	0,00	0,00
85,00	0,00	12,82	0,00	0,00	0,00	12,82