

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface.

Light Distribution: Direct.

Light Source: TC-DEL (G24q-2/G24q-3) lamp.

Control Gear: Electronic equipment
220-240VAC-50/60Hz.

Materials: Body: Spun aluminium.
Bezel: Die cast aluminium.

Surface Finish: Powder coated.



PB - Polished aluminium reflector | 110 Beam angle.

LAMP*	UGR	⚡	W	η(%)	AxB (mm)	Kg	HF	DSI	DALI
TC-DEL	≤19	G24q-2	1x18	80	Ø242x168	1,5	90008.E118.A	90008.E118.C	90008.E118.D
	≤22	G24q-3	1x26	80	Ø242x168	1,5	90008.F126.A	90008.F126.C	90008.F126.D
	≤22	G24q-2	2x18	76	Ø242x168	1,5	90008.E218.A	90008.E218.C	90008.E218.D
	≤22	G24q-3	2x26	67	Ø242x168	1,5	90008.F226.A	90008.F226.C	90008.F226.D


COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
601	Decorative glass.
602	Transparent glass.
603	Opal glass.
--	Lamps as optional.

DIMENSIONS




* Lamp not included.

Example code for order: 90008.E218.D (DALI) + W (COLOUR/FINISH) + 603 (OPTIONS)


We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

CROLL 2x18W PB
Lamp: 2 x TC-DEL 18W/840



CROLL 2x26W PB
Lamp: 2 x TC-DEL 26W/840



TO SPECIFY:

Surface mounted compact fluorescent downlight, single/ twin (horizontal only) 18/26W TC-DEL lamp. Spun aluminium body, die cast aluminium bezel and polished aluminium reflector. Optional tempered glass - as Indelague CROLL.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.