



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: TC-TEL (GX24q-1) or (GX24q-2) lamp.

Control Gear: Electronic equipment
220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 70° Beam angle

LAMP*	UGR		W	η(%)	AxBxC (mm)		Kg	HF	DSI	DALI
TC-TEL	≤19	GX24q-1	1x13	67	135x135x88	122x117	0,44	90005.G113.A	--	--
	≤19	GX24q-2	1x18	61	135x135x88	122x117	0,44	90005.H118.A	90005.H118.C	90005.H118.D

PM - Satin aluminium reflector | 70° Beam angle

LAMP*	UGR		W	η(%)	AxBxC (mm)		Kg	HF	DSI	DALI
TC-TEL	≤19	GX24q-1	1x13	63	135x135x88	122x117	0,44	90120.G113.A	--	--
	≤19	GX24q-2	1x18	58	135x135x88	122x117	0,44	90120.H118.A	90120.H118.C	90120.H118.D

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
--	Emergency unit 3 hours.
--	Lamps as optional.

DETAILS



Ballast Detail

* Lamp not included.


Example code for order: 90005.H118.D (DALI) + W (COLOUR/FINISH)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.



PHOTOMETRY

DIMENSIONS

DKN 1x13W PM
Lamp: 1 x TC-TEL 13W/840



DKN 1x13W PB
Lamp: 1 x TC-TEL 13W/840



TO SPECIFY:

Recessed square single compact fluorescent 13/18W downlight with steel sheet bezel and aluminium reflector. For ceiling thicknesses of 1-20mm – as Roxo Lighting DKN.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.