



Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: TC-TEL (GX24q-1) or (GX24q-2) lamp.

Optical System: Diffuser: Transparent tempered glass.

Control Gear: Electronic equipment
220-240VAC-50/60Hz.

Materials: Body: Steel sheet.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 70° Beam angle

LAMP*	UGR		W	η(%)	AxBxC (mm)		Kg	HF	DSI	DALI
TC-TEL	≤19	GX24q-1	1x13	59	135x135x91	121x121	0,69	90116.G113.A	--	--
	≤19	GX24q-2	1x18	53	135x135x91	121x121	0,69	90116.H118.A	90116.H118.C	90116.H118.D


COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
003	Opal glass.
--	Emergency unit 3 hours.
--	Lamps as optional.

DIMENSIONS



DETAILS



Ballast detail



Easy to change lamps

* Lamp not included.

Example code for order: 90116.H118.D (DALI) + W (COLOUR/FINISH) + 003 (OPTIONS)



We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

ROXO LIGHTING LIMITED

24 BEDFORD ROW | LONDON | WC1R 4TQ

roxo.london@roxolighting.com | www.roxolighting.com

PHOTOMETRY



TO SPECIFY:

Recessed IP54 single compact fluorescent 13/18w downlight with steel sheet bezel and aluminium reflector. Transparent 4mm tempered glass as standard and optional opal 4mm tempered glass. For ceiling thicknesses of 1-20mm - as Roxo Lighting DKN /G.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.