




Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application:	Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.
Mounting:	Ceiling recessed.
Light Distribution:	Direct.
Light Source:	LED 4000K, CRI >80, 50.000h life.
Optical System:	Diffuser: Opal tempered glass.
Control Gear:	LED driver, 220-240VAC-50/60Hz.
Surface Finish:	Powder coated.

PB - Polished aluminium reflector

LED	UGR	W	Lm	mA	V	Lm/W	η(%)	AxB (mm)	⌀	Kg	HF	DSI	DALI
	≤19	15	2300	350	40.5	114	79	Ø236x168	Ø215	2,3	90136.L115.E	90136.L115.G	90136.L115.H
	≤22	25	3400	600	44	94	80	Ø236x168	Ø215	2,3	90136.L125.E	90136.L125.G	90136.L125.H
	≤22	33	4300	700	45	94	79	Ø236x168	Ø215	2,3	90136.L133.E	90136.L133.G	90136.L133.H


COLOUR / FINISH

Code	Description
W	Matt white (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
3000	Colour temperature 3000K.
004	DAM - Microprismatic diffuser.
K3	Emergency unit 3 hours .
K1	Emergency unit 1 hour.

DIMENSIONS



DETAILS



Bracket detail



Passive cooling




Driver detail

Example code for order: 90136.L133.H (DALI) + W (COLOUR/FINISH)


We reserve the right to make technical changes without prior notice.

PHOTOMETRY

DYNA IP LED 25W PB



DYNA IP LED 25W PB 004



TO SPECIFY:

IP54 recessed LED round downlight with die cast aluminium bezel and aluminium reflector. Integral 2300/3400/4300 lumen light engine. Opal 4mm tempered glass as standard and optional microprismatic diffuser, 3000K and 1 or 3 hours emergency available. For ceiling thicknesses of 1-20mm - as Roxo Lighting DYNA IP LED.