

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: TC-DEL (G24q-2/G24q-3) lamp or TC-TEL (GX24q-3/GX24q-4) lamp.

Control Gear: Electronic equipment 220-240VAC-50/60Hz.

Materials: Body: Die cast aluminium.

Surface Finish: Powder coated.

PB - Polished aluminium reflector | 110 Beam angle

LAMP*	UGR		W	η(%)	AxB (mm)	∅	Kg	HF	DSI	DALI
TC-DEL	≤19	G24q-2	1x18	80	Ø236x146	Ø220	1	90022.E118.A	90022.E118.C	90022.E118.D
	≤22	G24q-3	1x26	80	Ø236x146	Ø220	1	90022.F126.A	90022.F126.C	90022.F126.D
	≤22	G24q-2	2x18	76	Ø236x146	Ø220	1,1	90022.E218.A	90022.E218.C	90022.E218.D
	≤22	G24q-3	2x26	67	Ø236x146	Ø220	1,1	90022.F226.A	90022.F226.C	90022.F226.D
TC-TEL	≤22	GX24q-3	1x32	74	Ø236x146	Ø220	1,2	90022.I132.A	90022.I132.C	90022.I132.D
	≤25	GX24q-4	1x42	88	Ø236x146	Ø220	1,2	90022.J142.A	90022.J142.C	90022.J142.D
	≤25	GX24q-3	2x32	61	Ø236x146	Ø220	1,5	90022.I232.A	90022.I232.C	90022.I232.D
	≤25	GX24q-4	2x42	56	Ø236x146	Ø220	1,5	90022.J242.A	90022.J242.C	90022.J242.D

COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
CL2	Class II.
601	Decorative glass.
602	Transparent glass.
603	Opal glass.
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.
--	Lamps as optional.

DETAILS



Ballast detail

* Lamp not included.


Example code for order: 90022.F226.D (DALI) + W (COLOUR/FINISH) + 601 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.



PHOTOMETRY

DIMENSIONS

DYNA 1x18W PB
Lamp: 1 x TC-DEL 18W/840



DYNA 2x18W PB
Lamp: 2 x TC-DEL 18W/840



TO SPECIFY:

Recessed round single/twin lamp 18/26W TC-DEL or 32/42W TC-TEL compact fluorescent downlight. Die cast aluminium bezel and polished aluminium reflector. Optional class II, decorative/transparent/opal tempered glass and 1 or 3 hours emergency available. For ceiling thicknesses of 1-25mm – as Indelague DYNA.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.