

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: TC-DEL (G24q-2/G24q-3) lamp or TC-TEL (GX24q-3/GX24q-4) lamp.

Optical System: Diffuser: Transparent tempered glass.

Control Gear: Electronic equipment 220-240VAC-50/60Hz.

Materials: Body: Die cast aluminium.

Surface Finish: Powder coated.

PB - Polished aluminium reflector

LAMP*	UGR	W	W	η(%)	AxB (mm)	Φ	Kg	HF	DSI	DALI
TC-DEL	≤19	G24q-2	1x18	73	Ø236x144	Ø215	1,4	90015.E118.A	90015.E118.C	90015.E118.D
	≤19	G24q-3	1x26	67	Ø236x144	Ø215	1,4	90015.F126.A	90015.F126.C	90015.F126.D
	≤19	G24q-2	2x18	65	Ø236x144	Ø215	1,5	90015.E218.A	90015.E218.C	90015.E218.D
	≤22	G24q-3	2x26	56	Ø236x144	Ø215	1,5	90015.F226.A	90015.F226.C	90015.F226.D
TC-TEL	≤22	GX24q-3	1x32	63	Ø236x144	Ø215	1,5	90015.I132.A	90015.I132.C	90015.I132.D
	≤22	GX24q-4	1x42	64	Ø236x144	Ø215	1,5	90015.J142.A	90015.J142.C	90015.J142.D
	≤22	GX24q-3	2x32	51	Ø236x144	Ø215	1,6	90015.I232.A	90015.I232.C	90015.I232.D
	≤22	GX24q-4	2x42	44	Ø236x144	Ø215	1,6	90015.J242.A	90015.J242.C	90015.J242.D


COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)


OPTIONS

Code	Description
CL2	Class II.
001	Decorative glass.
002	Opal glass.
K3	Emergency unit 3 hours .
K1	Emergency unit 1 hour.
--	Lamps as optional.

DIMENSIONS



DETAILS



Bracket detail

* Lamp not included.

Example code for order: 90015.E118.D (DALI) + W (COLOUR/FINISH) + 002 (OPTIONS)


We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.




Ballast detail

PHOTOMETRY

DYNA IP 1x18W PB
Lamp: 1 x TC-DEL 18W/840



DYNA IP 2x26W PB
Lamp: 2 x TC-DEL 26W/840



TO SPECIFY:

Recessed round single/twin lamp 18/26W TC-DEL or 32/42W TC-TEL compact fluorescent downlight. Die cast aluminium bezel with transparent tempered glass and polished aluminium reflector. Optional class II, decorative/opal tempered glass and 1 or 3 hours emergency available. For ceiling thicknesses of 1-20mm – as Roxo Lighting DYNA IP.