



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Storehouses, Industrial areas, Corridors, Garages, Basements.

Mounting: Surface/Wall Mounted.

Light Distribution: Direct.

Light Source: T5 (G5).

Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Polyester reinforced with fiberglass, manufactured by compression and polyurethane gasket.

Surface Finish: Gear tray powder coated in white.

Fixing system: Equipped with plastic clips and stainless steel fixing brackets.


DC0 - Polycarbonate diffuser

LAMP*	W	Lm/W	η(%)	AxBxC (mm)	K1	K3	Kg	HF	DALI
T5	1x28	73	85	1282x101x101	•	-	2,5	9C44.128.12.A4	9C44.128.12.74
	1x35	75	85	1578x101x101	•	•	3	9C44.135.12.A4	9C44.135.12.74
	1x49	67	83	1578x101x101	•	•	3	9C44.149.12.A4	9C44.149.12.74
	1x54	63	80	1282x101x101	•	-	2,5	9C44.154.12.A4	9C44.154.12.74
	1x80	55	76	1578x101x101	•	•	3	9C44.180.12.A4	9C44.180.12.74
	2x28	70	81	1282x101x101	•	•	3,3	9C44.228.12.A4	9C44.228.12.74
	2x35	71	81	1578x101x101	•	•	4	9C44.235.12.A4	9C44.235.12.74
	2x49	59	72	1578x101x101	•	•	4	9C44.249.12.A4	9C44.249.12.74
	2x54	54	68	1282x101x101	•	•	3,3	9C44.254.12.A4	9C44.254.12.74

OPTIONS

Code	Description
DM0	Methacrylate diffuser (DM0).
C/FI	Stainless steel clips.
9803	Aluminium background reflector.
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.
--	Lamps as optional.

DIMENSIONS



* Lamp not included
Example code for order: 9C44.135.12.74 (DALI) + DM0 + C/FI (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.


DETAILS



Optional stainless steel clips




Stainless steel adjustable fixing bracket for ceiling mounted version




Stainless steel fixing bracket with triangular holder for suspended version

PHOTOMETRY

ECF 1x28W DCO
Lamp: 1 x 28W/840 HE



ECF 2x28W DCO
Lamp: 2 x 28W/840 HE



TO SPECIFY:

Waterproof luminaire IP66 in polyester reinforced with fiberglass, manufactured by compression and polyurethane gasket. □ Polycarbonate diffuser with plastic clips and stainless steel fixing brackets. Available with single 28/35/49/54/80W or twin 28/35/49/54W T5(G5) fluorescent lamps. Optional stainless steel clips, dimmable versions and 1 or 3 hours emergency available - as Roxo Lighting ECF.