



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Storehouses, Industrial areas, Corridors, Garages, Basements.

Mounting: Surface/Wall Mounted.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, 50.000h life (@L80, B10, Ta 25 C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Polyester reinforced with fiberglass, manufactured by compression and polyurethane gasket.


Surface Finish: White matt powder coated gear tray.

Fixing system: Stainless steel fixing brackets and clips.

DC0 - Polycarbonate diffuser


LAMP	W	Lm	Lm/W	η(%)	AxBxC (mm)	D (mm)	K1	K3	Kg	HF	DALI
LED	15	1800	112	93	665x101x101	390	-	-	1,3	9044.113.12.F4	9044.113.12.E4
	29	3600	115	93	1282x101x101	800	•	•	2,3	9044.125.12.F4	9044.125.12.E4
	36	4520	121	96	1578x101x101	1100	•	•	2,7	9044.131.12.F4	9044.131.12.E4
	29	3600	108	87	665x145x101	390	-	-	1,7	9044.213.12.F4	9044.213.12.E4
	51	7200	128	91	1282x145x101	800	•	•	2,9	9044.225.12.F4	9044.225.12.E4
	66	9040	126	92	1578x145x101	1100	•	•	3,4	9044.231.12.F4	9044.231.12.E4

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code
3000

Light and presence sensor



Light and presence sensor

Order code
PIR

Example code for order: 9044.231.12.E4 (DALI) + 3000 + PIR (OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

Connector kit



KIT 3-pole IP68 connector
KIT 5-pole IP68 connector

Order code
966100
966200

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

Order code
K3
K1

• Includes test function by Telecommand signal.

DETAILS



Gear tray detail




Plastic clips




Stainless steel fixing brackets for ceiling mounted or suspended versions

PHOTOMETRY



ECF LED 29W
(1282x101mm) DC0 4000K



ECF LED 51W
DC0 4000K

TO SPECIFY:

LED waterproof luminaire, IP66 with polyester reinforced with fiberglass body, polyurethane gasket and polycarbonate diffuser. Standard version with 4000K, CRI>80, 50000h lifetime (@ L80, B10, Ta 25 C) and equipped with plastic clips and stainless steel fixing brackets. Optional dimmable DALI driver, 3000K, light and presence sensor, IP68 connector and 1 or 3 hours emergency unit. - as Indelague ECF LED

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.