



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Storehouses/Industrial areas/Corridors/Garages/Basements.

Mounting: Surface/Suspended/Wall Mounted.

Light Distribution: Direct.

Light Source: T5 (G5) lamp.

Control Gear: Electronic equipment, 220-240VAC-50/60Hz.

Materials: Body: Injected polycarbonate and natural silicone gasket.

Surface Finish: Gear tray powder coated in white matt (RAL9016).

Fixing system: Equipped with stainless steel fixing brackets and clips.


DC0 - Polycarbonate diffuser

LAMP*	W	Lm/W	η(%)	AxBxC (mm)	K1	K3	Kg	HF	DALI
T5	1x14	62	86	665x100x90	-	-	1	9C45.114.12.A4	9C45.114.12.74
	1x24	57	81	665x100x90	-	-	1	9C45.124.12.A4	9C45.124.12.74
	1x28	75	88	1270x100x90	•	-	1,8	9C45.128.12.A4	9C45.128.12.74
	1x35	74	85	1570x100x90	•	•	2,1	9C45.135.12.A4	9C45.135.12.74
	1x49	70	85	1570x100x90	•	•	2,1	9C45.149.12.A4	9C45.149.12.74
	1x54	62	79	1270x100x90	•	-	1,8	9C45.154.12.A4	9C45.154.12.74
	1x80	57	79	1570x100x90	•	•	2,1	9C45.180.12.A4	9C45.180.12.74
	2x14	58	78	665x140x90	-	-	1,4	9C45.214.12.A4	9C45.214.12.74
	2x24	54	75	665x140x90	-	-	1,4	9C45.224.12.A4	9C45.224.12.74
	2x28	75	86	1270x140x90	•	•	2,4	9C45.228.12.A4	9C45.228.12.74
	2x35	75	86	1570x140x90	•	•	2,8	9C45.235.12.A4	9C45.235.12.74
	2x49	71	87	1570x140x90	•	•	2,8	9C45.249.12.A4	9C45.249.12.74
	2x54	59	75	1270x140x90	•	•	2,4	9C45.254.12.A4	9C45.254.12.74

OPTIONS

Code	Description
PIR	Light and presence sensor..
CRET	IP65 connector.
9803	Aluminium background reflector.
K3	Emergency unit 3 hours.
K1	Emergency unit 1 hour.
P/LED	Electrification for LED lamp (T8).
--	Lamps as optional.

DIMENSIONS



* Lamp not included

Example code for order: 9C45.128.12.A4 (HF) + K1 (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

DETAILS




Stainless steel clips




Stainless steel fixing brackets for ceiling mounted or suspended versions

PHOTOMETRY

ECP 1x28W DC0
Lamp: 1 x 28W/840 HE



ECP 2x28 DC0
Lamp: 2 x 28W/840 HE



TO SPECIFY:

Waterproof IP65 luminaire with injected polycarbonate body and natural silicone gasket. Polycarbonate diffuser with stainless steel clips and fixing brackets. Available with single 14/24/28/35/49/54/80W or twin 14/24/28/35/49/54W T5(G5) fluorescent lamps. Optional dimmable versions and 1 or 3 hours emergency available - as Roxo Lighting ECP.