



Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface.

Light Distribution: Direct.

Light Source: TC-DEL (G24q-1/G24q-2/G24q-3) lamp.

Control Gear: Electronic equipment
220-240VAC-50/60Hz.

Materials: Body: Spun aluminium.
Bezel: Die cast aluminium.

Surface Finish: Powder coated.

PB - Polished aluminium reflector.

LAMP*		W	AxB (mm)	Kg	ORDER CODE
TC-DEL	G24q-1	1x13	Ø174x214	0,9	90009.D113.A
	G24q-2	1x18	Ø174x214	0,9	90009.E118.A
	G24q-3	1x26	Ø174x214	0,9	90009.F126.A


COLOUR / FINISH

Code	Description
W	White (RAL 9016)
B	Black (RAL 9005)
G	Grey (RAL 9006)

OPTIONS

Code	Description
701	Decorative glass.
702	Transparent glass.
703	Opal glass.
--	Lamps as optional.

DIMENSIONS




* Lamp not included.

Example code for order: 90009.D113.A (ORDER CODE) + W (COLOUR/FINISH) + 703 (OPTIONS).

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

ELEEX 1x18W PB
Lamp. 1 x TC-DEL 13W/840



TO SPECIFY:

Surface mounted compact fluorescent downlight, single (vertical only) 13/18/26W TC-DEL lamp. Spun aluminium body, die cast aluminium bezel and polished aluminium reflector. Optional tempered glass - as Indelague ELEEX.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.