



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).

Optical System: Reflector: Polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
	≤25	7	747	107	90681.L240.E.0020	90681.L240.H.0020
	≤25	11	1168	106	90680.L240.E.0020	90680.L240.H.0020

Polycarbonate reflector - 50

LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
	≤25	7	724	103	90681.L240.E.0050	90681.L240.H.0050
	≤28	11	1144	104	90680.L240.E.0050	90680.L240.H.0050

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

DIMENSIONS



OPTIONS

Temperatura de cor


Código




3000K

3000

PHOTOMETRY



ELI 50 /C 4000K 20°
HO



ELI 50 /C 4000K 50°
HO

TO SPECIFY:

Circular downlight, 50mm diameter, with direct LED lighting, for ceiling surface application. Available with 20° and 50° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 1168Lm. LED with 106Lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@L80, B10, Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Indelague ELI-50 /C.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.