



**LED**

Norms: EN 60598-1, EN 60598-2-2



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).


**Optical System:** Reflector: Polycarbonate.

**Control Gear:** Not included.


**Materials:** Body: Aluminium.

**Surface Finish:** Powder coated epoxy polyester.

Polycarbonate reflector - 20

 LED	UGR	W	Lm Output	mA	Lm/W	Order code
	≤25	10	1494	300	149	90695.L002.0020
	≤25	17	2336	500	137	90694.L002.0020

Polycarbonate reflector - 50


 LED	UGR	W	Lm Output	mA	Lm/W	Order code
	≤25	10	1448	300	145	90695.L002.0050
	≤28	17	2288	500	135	90694.L002.0050

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

### COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

### DIMENSIONS



### OPTIONS

#### Colour temperature



3000K

Order code

**3000**

#### Safety cable



Steel safety cable

Order code

**955010**

#### LED Driver On/Off



LED Driver, 220-240VAC-50-60Hz  
DRIVER 12,6W 10-42V 300mA HF (On/Off)  
DRIVER 21W 10-42V 500mA HF (On/Off)

Order code

**900003E**  
**900007E**

#### LED Driver DALI/Push




LED Driver, 220-240VAC-50-60Hz  
DRIVER 15,6W 09-52V 300MA DALI+PUSH  
DRIVER 26W 09-52V 500MA DALI+PUSH


Order Code

**900103H**  
**900107H**

### PHOTOMETRY



ELI 50 /E2 4000K 20°



ELI 50 /E2 4000K 50°

#### TO SPECIFY:

Circular double downlight, 135x75 mm diameter, with direct LED lighting, for recessed application. Available with 20° and 50° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 2336 lm. LED with 152 lm/W efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@L80, B10, Ta 25 C). 3000K version available as options. - as Roxo Lighting ELI-50 /E 2.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.