



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Surface.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).

Optical System: Reflector: Polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
	≤25	7	747	107	90701.L100.E.0020	90701.L100.H.0020
	≤25	11	1168	106	90700.L100.E.0020	90700.L100.H.0020

Polycarbonate reflector - 50


LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
	≤25	7	724	103	90701.L100.E.0050	90701.L100.H.0050
	≤28	11	1144	104	90700.L100.E.0050	90700.L100.H.0050

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

DIMENSIONS



OPTIONS

Colour temperature


Order code




3000K

3000

PHOTOMETRY



ELI 50 SPOT /C 4000K 20° HO



ELI 50 Spot /C 4000K 50° HO

TO SPECIFY:

LED luminaire, with Ø80 mm spotlight, 190° rotatable and ±90° tiltable, for surface mounted application. Possibility of 20° and 50° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 1168 lm. LED with 116 lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 60.000h lifetime (@L80, B10, Ta 25 °C). DALI dimming and 3000K available as options. - as Indelague ELI-50 SPOT /C.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.