



**LED**

Norms: EN 60598-1, EN 60598-2-2



## PRODUCT DESCRIPTION

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Recessed.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).

**Optical System:** Reflector: Polycarbonate.

**Control Gear:** Not included.

**Materials:** Body: Aluminium.

**Surface Finish:** Powder coated epoxy polyester.

### Polycarbonate reflector - 20



LED	UGR	W	Lm Ouput	mA	Lm/W	Order code
	≤25	5	747	150	149	90703.L001.0020
	≤25	9	1168	250	130	90702.L001.0020

### Polycarbonate reflector - 50




LED	UGR	W	Lm Ouput	mA	Lm/W	Order code
	≤25	5	724	150	145	90703.L001.0050
	≤28	9	1144	250	127	90702.L001.0050

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

## COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

## DIMENSIONS



## OPTIONS

### Colour temperature



3000K

Order code

**3000**

### Safety cable



Steel safety cable

Order code

**955010**

### LED Driver On/Off



LED Driver, 220-240VAC-50-60Hz  
DRIVER 6,3W 10-42V 150mA HF (On/Off)  
DRIVER 10,5W 10-42V 250mA HF (On/Off)

Order code

**900000E**

**900002E**

### LED Driver DALI/Push




LED Driver, 220-240VAC-50-60Hz  
DRIVER 7,8W 09-52V 150mA DALI+PUSH  
DRIVER 13W 09-52V 250mA DALI+PUSH

Order Code


**900100H**

**900102H**

## PHOTOMETRY



ELI 50 Spot/E1 4000K 20°



ELI 50 Spot/E1 4000K 50°

### TO SPECIFY:

LED luminaire, with Ø50mm spotlight, 190° rotatable and ±90° tiltable, for recessed application. Possibility of 20° and 50° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 1168 lm. LED with 152 lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 60.000h lifetime (@L80, B10, Ta 25°C). 3000K available as options. - as Indelague ELI-50 SPOT /E 1.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.