



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Recessed.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).


Optical System: Reflector: Polycarbonate.

Control Gear: Not included.


Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

	LED	UGR	W	Lm Ouput	mA	Lm/W	Order code
		≤25	5	747	150	149	90703.L001.0020
		≤25	9	1168	250	130	90702.L001.0020

Polycarbonate reflector - 50


	LED	UGR	W	Lm Ouput	mA	Lm/W	Order code
		≤25	5	724	150	145	90703.L001.0050
		≤28	9	1144	250	127	90702.L001.0050

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code

3000

Safety cable



Steel safety cable

Order code

955010

LED Driver On/Off



LED Driver, 220-240VAC-50-60Hz
DRIVER 6,3W 10-42V 150mA HF (On/Off)
DRIVER 10,5W 10-42V 250mA HF (On/Off)

Order code

900000E

900002E

LED Driver DALI/Push




LED Driver, 220-240VAC-50-60Hz
DRIVER 7,8W 09-52V 150mA DALI+PUSH
DRIVER 13W 09-52V 250mA DALI+PUSH

Order Code


900100H

900102H

PHOTOMETRY



ELI 50 Spot /E1 4000K 20°



ELI 50 Spot /E1 4000K 50°

TO SPECIFY:

LED luminaire, with Ø50mm spotlight, 190° rotatable and ±90° tiltable, for recessed application. Possibility of 20° and 50° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 1168 lm. LED with 152 lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 60.000h lifetime (@L80, B10, Ta 25 C). 3000K available as options. - as Roxo Lighting ELI-50 SPOT /E 1.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.