



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Recessed.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).


Optical System: Reflector: Polycarbonate.

Control Gear: Not included.


Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

LED	UGR	W	Lm Output	mA	Lm/W	Order code
	≤25	10	1494	300	149	90703.L002.0020
	≤25	17	2336	500	137	90702.L002.0020

Polycarbonate reflector - 50


LED	UGR	W	Lm Output	mA	Lm/W	Order code
	≤25	10	1448	300	147	90703.L002.0050
	≤28	17	2288	500	135	90702.L002.0050

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
☐ W	White
■ B	Black

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code

3000

Safety cable



Steel safety cable

Order code

955010

LED Driver On/Off



LED Driver, 220-240VAC-50-60Hz
DRIVER 12.6W 10-42V 300mA HF (On/Off)
DRIVER 21W 10-42V 500mA HF (On/Off)

Order code

900003E

900007E

LED Driver DALI/Push




LED Driver, 220-240VAC-50-60Hz
DRIVER 15.6W 09-52V 300MA DALI+PUSH
DRIVER 26W 09-52V 500MA DALI+PUSH

Order Code


900103H

900107H

PHOTOMETRY



ELI 50 Spot /E2 4000K 20°



ELI 50 SPOT /E2 4000K

TO SPECIFY:

LED luminaire, with two Ø80mm spotlights, 190° rotatable and ±90° tilttable, for recessed application. Possibility of 20° and 50° reflector for different light projection. Steel sheet and aluminium body, powder-coated with epoxy polyester, available in white, gray and black colours. Flux of 2336 lm. LED with 152 lm/W efficacy. Standard version with 4000K LED, CRI >90, MacAdam Step <3 and 60.000h lifetime (@L80, B10, Ta 25 C). 3000K available as options. - as Roxo Lighting ELI-50 SPOT /E 2.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.