



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Direct / Indirect.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).

Optical System: Reflector: Polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

LED	UGR	W	Lm Output	Lm/W	HF	DALI
	≤25	10	1254	125	90692.L260.E.0020	90692.L260.H.0020

Polycarbonate reflector - 50


LED	UGR	W	Lm Output	Lm/W	HF	DALI
	≤28	10	1214	121	90692.L260.E.0050	90692.L260.H.0050

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

DIMENSIONS



OPTIONS

Colour temperature


Order code




3000K

3000

PHOTOMETRY



ELI 50 Sq /W D/I 4000K
20° HO



ELI 50 Sq /W D/I 4000K
50° HO

TO SPECIFY:

Square downlight, 50x50mm, with direct and indirect LED lighting, for wall application. Available with 20° and 50° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 2336 lm. LED with 111 lm/W efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@L80, B10, Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Indelague ELI-50 SQ /W D/I.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.