



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).


Optical System: Reflector: Polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

	LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
		≤25	7	747	107	90687.L240.E.0020	90687.L240.H.0020
		≤25	11	1168	106	90686.L240.E.0020	90686.L240.H.0020

Polycarbonate reflector - 50

	LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
		≤25	7	724	103	90687.L240.E.0050	90687.L240.H.0050
		≤28	11	1144	104	90686.L240.E.0050	90686.L240.H.0050


• To complete the product, add current supply cable and ceiling rose. Please order separately.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black

DIMENSIONS



Recessed ceiling rose
T47 Q50



Surface mounted ceiling rose
T46 Q50



OPTIONS

Colour temperature




3000K

Order code

3000

Ceiling rose



Ceiling rose
Surface mounted T46 Q50
Recessed T47 Q50

Order code

978807

978808

• To order this option you must indicate the desired colour

Current supply cable 1,5 m



1,5 m transparent cable
3 x 0,75 mm
5 x 0,75 mm

Order code

940400

940500

Current supply cable 3 m



3 m transparent cable
3 x 0,75 mm
5 x 0,75 mm

Order code

940401

940501

Current supply cable 6 m



6 m transparent cable
3 x 0,75 mm
5 x 0,75 mm


Order code

940402


940507

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



ELI 50 Sq 4000K 20°
HO



ELI 50 Sq 4000K 50°
HO

TO SPECIFY:

Square downlight, 80x80mm, with direct LED lighting, for suspended application. Available with 20° and 50° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 1168 lm. LED with 106 lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@L80, B10, Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Roxo Lighting ELI-50 SQ.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.