



Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Wall Mounted.

**Light Distribution:** Direct / Indirect.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L70, B50, Ta 25 C).

**Optical System:** Reflector: Polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Aluminium.

**Surface Finish:** Revestido a epoxi poliéster.

Polycarbonate reflector - 20



LED	UGR	W	Lm Output	Lm/W	HF	DALI
	≤25	10	1254	125	90684.L260.E.0020	90684.L260.H.0020

Polycarbonate reflector - 50



LED	UGR	W	Lm Output	Lm/W	HF	DALI
	≤28	10	1214	118	90684.L260.E.0050	90684.L260.H.0050

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
W	White
B	Black

DIMENSIONS



OPTIONS

Colour temperature




3000K


Order code

3000

PHOTOMETRY



ELI 50 /W D/I 4000K  
20° HO



ELI 50 /W D/I 4000K  
50° HO

TO SPECIFY:

Circular downlight, 50mm diameter, with direct and indirect LED lighting, for wall application. Available with 20° and 50° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 2336 lm in HO. LED with 111 lm/W efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@70,B50,Ta 25 °C). Dimmable DALI driver and 3000K version available as options. as Roxo Lighting ELI-50 /W D/I.