



**LED**

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).

**Optical System:** Reflector: Polycarbonate.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.


**Materials:** Body: Aluminium.

**Surface Finish:** Powder coated epoxy polyester.

Polycarbonate reflector - 20

	LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
		≤25	7	747	107	90679.L240.E.0020	90679.L240.H.0020
		≤25	11	1168	106	90678.L240.E.0020	90678.L240.H.0020

Polycarbonate reflector - 50

	LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
		≤25	7	724	103	90679.L240.E.0050	90679.L240.H.0050
		≤28	11	1144	104	90678.L240.E.0050	90678.L240.H.0050


• To complete the product, add current supply cable and ceiling rose. Please order separately.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**COLOUR / FINISH**

Code	Description
□ W	White
■ B	Black

**DIMENSIONS**



**Recessed ceiling rose T42 D50**



**Surface mounted ceiling rose T41 D50**



**OPTIONS**

**Colour temperature**



3000K

Order code

**3000**

**Ceiling rose**



Ceiling rose  
Surface mounted T41 D50  
Recessed T42 D50

• To order this option you must indicate the desired colour

Order code

**978805**

**978804**

**Current supply cable 1,5 m**



1,5 m transparent cable  
3 x 0,75 mm  
5 x 0,75 mm

Order code

**940400**

**940500**

**Current supply cable 3 m**



3 m transparent cable  
3 x 0,75 mm  
5 x 0,75 mm

Order code

**940401**

**940501**

**Current supply cable 6 m**



6 m transparent cable  
3 x 0,75 mm  
5 x 0,75 mm


Order code

**940402**


**940507**

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

## PHOTOMETRY



ELI 50 4000K 20°  
HO



ELI 50 4000K 50°  
HO

### TO SPECIFY:

Circular downlight, 50mm diameter, with direct LED lighting, for suspended application. Available with 20 and 50 reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 1168Lm. LED with 106 lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@L80, B10, Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Indelague ELI-50.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.