



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial and Business areas, Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step <3, 60.000h lifetime (@L80, B10, Ta 25 C).


Optical System: Reflector: Polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

Polycarbonate reflector - 20

 LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
	≤25	7	747	107	90679.L240.E.0020	90679.L240.H.0020
	≤25	11	1168	106	90678.L240.E.0020	90678.L240.H.0020

Polycarbonate reflector - 50

 LED	UGR	W	Lm Ouput	Lm/W	HF	DALI
	≤25	7	724	103	90679.L240.E.0050	90679.L240.H.0050
	≤28	11	1144	104	90678.L240.E.0050	90678.L240.H.0050


• To complete the product, add current supply cable and ceiling rose. Please order separately.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
☐ W	White
■ B	Black

DIMENSIONS



Recessed ceiling rose
T42 D50



Surface mounted ceiling rose
T41 D50



OPTIONS

Colour temperature



3000K

Order code

3000

Ceiling rose



Ceiling rose
Surface mounted T41 D50
Recessed T42 D50


Order code

978805

978804

• To order this option you must indicate the desired colour

Current supply cable 1,5 m



1,5 m transparent cable
3 x 0,75 mm
5 x 0,75 mm

Order code

940400

940500

Current supply cable 3 m



3 m transparent cable
3 x 0,75 mm
5 x 0,75 mm

Order code

940401

940501

Current supply cable 6 m



6 m transparent cable
3 x 0,75 mm
5 x 0,75 mm


Order code

940402


940507

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



ELI 50 4000K 20°
HO



ELI 50 4000K 50°
HO

TO SPECIFY:

Circular downlight, 50mm diameter, with direct LED lighting, for suspended application. Available with 20 and 50 reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Flux of 1168Lm. LED with 106 lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 60.000h service life, (@L80, B10, Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Roxo Lighting ELI-50.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.