



LED

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Surface.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).

**Optical System:** Reflector: Polished aluminium.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Aluminium.

**Surface Finish:** Powder coated epoxy polyester.

PB - Polished reflector - 35

	LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
		≤19	10	1161	116	0,66	90596.L200.E.0035	90596.L200.H.0035

PB - Polished reflector - 60


	LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
		≤22	10	1161	116	0,66	90596.L200.E.0060	90596.L200.H.0060

This product's light source is Energy Class: E.

**COLOUR / FINISH**

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

**DETAILS**



Vista frontal

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

**OPTIONS**

Colour temperature

Order code




3000K


**3000**

**PHOTOMETRY**

**DIMENSIONS**



ELI /C PB 4000K 35°



ELI /C PB 4000K 60°



**TO SPECIFY:**

Circular downlight, 80mm diameter, with direct LED lighting, for ceiling surface application. Available with 35° and 60° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Luminous flux of 1161Lm and LED with 116Lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 65.000h service life, (@L90,B10,Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Roxo Lighting ELI /C.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.