

LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.


Light Source: LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.



PB - Polished reflector - 35

LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
	≤19	10	1161	116	0,49	90655.L001.E.0035	90655.L001.H.0035

PB - Polished reflector - 60


LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
	≤22	10	1161	116	0,49	90655.L001.E.0060	90655.L001.H.0060

This product's light source is Energy Class: E.

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

DETAILS



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code






3000K

3000

PHOTOMETRY

DIMENSIONS



We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.