

LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Ceiling recessed.

Light Distribution: Direct.


Light Source: LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.



PB - Polished reflector - 35

LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
	≤19	10	1161	116	0,49	90655.L001.E.0035	90655.L001.H.0035

PB - Polished reflector - 60


LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
	≤22	10	1161	116	0,49	90655.L001.E.0060	90655.L001.H.0060

This product's light source is Energy Class: E.

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

DETAILS



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code




3000K


3000

PHOTOMETRY


DIMENSIONS



ELI Sq /E 1 PB 4000K 35°



ELI Sq /E 1 PB 4000K 60°



TO SPECIFY:

Square downlight, 115x115 mm, with direct LED lighting, for recessed application. Available with 35° and 60° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Luminous flux of 1161Lm and LED with 116lm/W of maximum efficiency. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 65.000h service life, (@L90,B10,Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Indelague ELI SQ /E.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.