



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Wall Mounted.

Light Distribution: Direct / Indirect.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).


Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

PB - Polished reflector - 35

	LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
		≤13	10	1258	126	0,94	90653.L200.E.0035	90653.L200.H.0035

PB - Polished reflector - 60

	LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
		≤16	10	1244	124	0,94	90653.L200.E.0060	90653.L200.H.0060

This product's light source is Energy Class: E.

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input type="checkbox"/> B	Black

DETAILS



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code




3000K


3000

PHOTOMETRY


DIMENSIONS



ELI Sq /W D/I PB 4000K
35°



ELI Sq /W D/I PB 4000K
60°



TO SPECIFY:

Square downlight, 80x80mm, with direct and indirect LED lighting, for wall application. Available with 35° and 60° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Luminous flux of 1258Lm and LED with 126Lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 65.000h service life, (@L90,B10,Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Roxo Lighting ELI Sq /W D/I.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.