



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Wiring: Pre-wired 1,5m transparent cable.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

PB - Polished reflector - 35



UGR	W	Lm Output	Lm/W	kg	HF	DALI
≤19	10	1161	116	0,785	90566.L200.E.0035	90566.L200.H.0035

PB - Polished reflector - 60




UGR	W	Lm Output	Lm/W	kg	HF	DALI
≤22	10	1161	116	0,785	90566.L200.E.0060	90566.L200.H.0060

This product's light source is Energy Class: E.

COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black

DETAILS



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code


Suspension kit

Order code



3000K

3000




Suspension Kit
Surface mounted T25 Q100
Recessed T7 Q90

978610
971400


• To order this option you must indicate the desired colour

PHOTOMETRY


DIMENSIONS



ELI Sq PB 4000K 35°



ELI Sq PB 4000K 60°



Recessed ceiling rose
T7 Q90



Surface mounted ceiling rose
T25 Q100



TO SPECIFY:

Square downlight, 80x80mm, with direct LED lighting, for suspended application. Available with 35° and 60° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Luminous flux of 1161Lm and LED with 116Lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 65.000h service life, (@L90,B10,Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Indelague ELI Sq.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.