



LED

Norms: EN 60598-1, EN 60598-2-1



**PRODUCT DESCRIPTION**

**Areas of Application:** Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Suspended.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).

**Optical System:** Reflector: Polished aluminium.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Wiring:** Pre-wired 1,5m transparent cable.

**Materials:** Body: Aluminium.

**Surface Finish:** Powder coated epoxy polyester.

PB - Polished reflector - 35



UGR	W	Lm Output	Lm/W	kg	HF	DALI
≤19	10	1161	116	0,785	90566.L200.E.0035	90566.L200.H.0035

PB - Polished reflector - 60




UGR	W	Lm Output	Lm/W	kg	HF	DALI
≤22	10	1161	116	0,785	90566.L200.E.0060	90566.L200.H.0060

This product's light source is Energy Class: E.

**COLOUR / FINISH**

Code	Description
W	White
G	Grey
B	Black

**DETAILS**



Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

## OPTIONS

### Colour temperature

Order code


### Suspension kit

Order code



3000K

3000




Suspension Kit  
Surface mounted T25 Q100  
Recessed T7 Q90

978610  
971400


• To order this option you must indicate the desired colour

## PHOTOMETRY


## DIMENSIONS



ELI Sq PB 4000K 35°



ELI Sq PB 4000K 60°



Recessed ceiling rose  
T7 Q90



Surface mounted ceiling rose  
T25 Q100



### TO SPECIFY:

Square downlight, 80x80mm, with direct LED lighting, for suspended application. Available with 35° and 60° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Luminous flux of 1161Lm and LED with 116Lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 65.000h service life, (@L90,B10,Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Roxo Lighting ELI Sq.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.