



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

Mounting: Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>90, MacAdam Step<3, 65.000h life (@L90, B10, Ta 25 C).

Optical System: Reflector: Polished aluminium.

Control Gear: LED driver,220-240VAC-50/60Hz.

Materials: Body: Aluminium.

Surface Finish: Powder coated epoxy polyester.

PB - Polished reflector - 35

	LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
		≤19	10	1161	116	0,66	90564.L200.E.0035	90564.L200.H.0035

PB - Polished reflector - 60


	LED	UGR	W	Lm Output	Lm/W	kg	HF	DALI
		≤22	10	1161	116	0,66	90564.L200.E.0060	90564.L200.H.0060

This product's light source is Energy Class: E.

COLOUR / FINISH

Code	Description
<input type="checkbox"/> W	White
<input type="checkbox"/> G	Grey
<input checked="" type="checkbox"/> B	Black

DETAILS




Front view

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

OPTIONS

Colour temperature

Order code



3000K

3000

Suspension kit

Order code



Suspension Kit
Surface mounted T24 D95
Recessed T5 D90


978600

971300

• To order this option you must indicate the desired colour

Current supply cable

Order code




1,5 m transparent cable 0,75 mm²
3 x 0,75 mm²
5 x 0,75 mm²

940400


940500

PHOTOMETRY


DIMENSIONS



ELI PB 4000K 35°



ELI PB 4000K 60°



Recessed ceiling rose
T5 D90



Surface mounted ceiling rose
T24 D95



TO SPECIFY:

Circular downlight, 80mm diameter, with direct LED lighting, for suspended application. Available with 35 and 60° reflector for a different light projection. Extruded aluminium body, powder-coated with epoxy polyester and available in white, gray and black colours. Luminous flux of 1161Lm and LED with 116lm/W of maximum efficacy. Standard version with 4000K LED, CRI>90, MacAdam Step<3 and 65.000h service life, (@L90,B10,Ta 25 C). Dimmable DALI driver and 3000K version available as options. - as Roxo Lighting ELI.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.